

Rubino 200

Rubino 200 is the completely automatic table-top vending machine of the last generation with design and technical performance at the top of the category. It is specifically designed for small and medium locations.

Available with cabinet in two versions, standard and for payment system, it dispenses up to 8 different beverages.

Main features

- Automatically dispenses cups (up to 195), sugar and stirrers
- Saeco Brewing Unit: top quality of espresso, easy cleaning and maintenance
- Accepts the most commonly used parallel and serial MDB (possible Master and Slave configurations), BDV and Executive payment systems
- 6 gr to 9 gr adjustable doser
- Updated water circuit
- Standard CPU for the whole range
- Customizable settings
- High safety for customer and operator

Accessories

- Cabinet with height-adjustable feet (w x h x d 410 x 800 x 537 mm, 24 kg)
- Cabinet with height-adjustable feet suitable for change-giver (w x h x d 410 x 800 x 537 mm, 24 kg)
- Independent water tank kit
- Timekeeper kit
- Mixer kit for tea spiral replacement with decaffeinated/barley
- 12 V DC validator kit
- Electromechanical pulse counter kit
- 5-button keypad kit
- Memory key to copy and quickly transfer machine's settings
- Eva-Dts kit



Ideas with Passion

 **Saeco**



Technical data

Rubino 200

Dimensions (w x h x d)	410 x 757 x 537 mm
Weight	46 kg
Power supply	230 V/50 Hz - 120 V/60 Hz
Power consumption	1250 W
Boiler	brass
Water connection	3/4" (1 - 8 bar)
Water supply	standard: water-supply optional: independent water tank kit
Coffee bean container	1
Instant product container	3
Sugar container	1
Disc mixer	1
Spiral mixer	1
Brewing unit	7 gr - 9 gr
Available cups Ø	70 - 73 mm
Available stirrers	90 - 115 mm
Number of selections	8
Number of preselections	up to 4

Product capacity

Rubino 200

Coffee beans	2.0 kg
Instant coffee	0.7 kg
Milk	0.85 kg
Chocolate	1.7 kg
Tea	2.35 kg
Sugar	2.0 kg
Cups (h 70 mm)	195
Stirrers	180
Independent water tank	20 l



Technical specifications

- Pre-galvanized and painted steel-sheet body
- Thermoplastic door
- Thermoplastic cover with transparent coffee bean container
- Containers and tanks in food-contact-approved polypropylene
- Water, coffee and cup empty signal
- Software function setting the maximum number of coffee cycles permitted before the dump box is removed and emptied
- Electronically controlled boiler temperature
- Exhauster to absorb internal moisture and additional steam exhauster for the dispensing area
- Removable cup releasing device for easy cleaning and checking
- 60 W electromagnetic vibration pump
- Anti-overflow air-break device
- Simplified error reset
- Boiler safety valve
- General safety relay for 24 V components
- Thermal cut-outs on all devices supplied with line voltage
- CE, VDE and UL approved

User interface

- Direct access 8-button keypad for beverage selection
- 2 keys for sugar preselection
- Option to set 2 preselection keys: one for decaffeinated/barley and one for no-cup option
- 2-line, 20-character alphanumeric display



Always at your service:

Saeco Vending S.p.A.

Località Casona, 1066
40041 Gaggio Montano, Bologna - Italy
Tel: +39 0534 7741 - Fax: +39 0534 774808

info.saecovending@saeco.com
www.saeco.com